

Starter kits: SIRIUS ACT with PROFINET

Test the new communication solutions for the field and control panel

Top performance thanks to strong communication

SIRIUS ACT with PROFINET connects push buttons and signaling devices directly with the controller and HMI devices via PROFINET – including safety functions, with engineering and commissioning being simplified no end by the TIA Portal. Additional benefits include uniform data management, shorter downtimes thanks to faster fault diagnostics and option handling, which can be used to flexibly design plants and systems and even modify them during operation.

“Standard” starter kit – SIRIUS ACT with PROFINET Article No. 3SU1900-0XA10-0AA0



Scope of supply (from left to right):

Top: 1 standard Interface Module, 3 terminal modules, screwdriver

Middle: 4 holders, pair of scissors

Bottom: 1 selector, 1 illuminated push button, 1 button, 1 indicator light, flat ribbon cable

“Safety” starter kit – SIRIUS ACT with PROFINET Article No. 3SU1900-0XB10-0AA0



Scope of supply (from left to right):

Top: 1 fail-safe Interface Module, 3 terminal modules, screwdriver

Middle: 4 holders, pair of scissors

Bottom: 1 EMERGENCY STOP push button, 1 illuminated push button, 1 button, 1 indicator light, flat ribbon cable

Detailed installation information available at:

siemens.com/sirius-act-profinet-manual

The quick and easy route to peak performance

- Efficient PLC integration
- Reduced wiring outlay – fewer sources of error during installation and commissioning
- Quick installation with flat ribbon cable without special tools
- High degree of flexibility
 - Additional 4 digital inputs, 1 digital output (DI, DQ) and 1 analog input (AI)
 - Modular and plug-in design of all components
- Optionally with Safety Integrated – making it possible to integrate safety technology; e.g. emergency stop with safety-related Interface Module via PROFIsafe communication
- No addressing of individual push buttons and command points required – only one IP address for up to 21 devices
- Easy replacement of memory modules without programming knowledge
- Extended diagnostic and parameterization options and end-to-end engineering when integrated into the TIA Portal

SIRIUS ACT with PROFINET at a glance

Product	Version	Article number	
Push buttons and signaling devices	Multiple versions available	3SU10□□-□□□□-□□□□	
PROFINET Interface Modules 	Standard IM, 24 V DC, 1–20 TMs connectable	Screw terminals: 3SU1400-1LK10-1AA1 Spring-type terminals: 3SU1400-1LK10-3AA1	
	Fail-safe IM F, 24 V DC, 1–20 TMs connectable	Screw terminals: 3SU1400-1LL10-1BA1 Spring-type terminals: 3SU1400-1LL10-3BA1	
	PROFINET terminal modules 	“Commands” TM with 2 spring contacts	3SU1400-1MA10-1BA1
		“Commands and LED” TM with 2 spring contacts and integrated LED	Red LED
Yellow LED			3SU1401-1MC30-1CA1
Green LED			3SU1401-1MC40-1CA1
Blue LED			3SU1401-1MC50-1CA1
White LED			3SU1401-1MC60-1CA1
“LED” TM with integrated LED		Amber LED	3SU1401-1MC00-1CA1
		Red LED	3SU1401-1ME20-1DA1
		Yellow LED	3SU1401-1ME30-1DA1
		Green LED	3SU1401-1ME40-1DA1
	Blue LED	3SU1401-1ME50-1DA1	
Accessories 	Memory module for storage of configuration data	Optional for IM, included for IM F: 3RK3931-0AA00	
	LED module, only illuminated for IM/IM F and SIRIUS ACT	Red LED	3SU1401-3BA20-5AA0
		Yellow LED	3SU1401-3BA30-5AA0
		Green LED	3SU1401-3BA40-5AA0
		Blue LED	3SU1401-3BA50-5AA0
		White LED	3SU1401-3BA60-5AA0
	Flat ribbon cable, 7-core	Amber LED	3SU1401-3BA00-5AA0
Cable length 5 m		3SU1900-0KQ80-0AA0	
	Cable length 10 m	3SU1900-0KP80-0AA0	

You can find all the information at:

[siemens.com/sirius-act-profinet](https://www.siemens.com/sirius-act-profinet)

Technical specifications:

[siemens.com/sios](https://www.siemens.com/sios)

Product selection and ordering:

[siemens.com/industrymall](https://www.siemens.com/industrymall)

[siemens.com/sirius-act/configurator](https://www.siemens.com/sirius-act/configurator)

Subject to changes and errors. The information given in this document only contains general descriptions and/or performance features which may not always specifically reflect those described, or which may undergo modification in the course of further development of the products. The requested performance features are binding only when they are expressly agreed upon in the concluded contract.

Siemens AG
Digital Factory
Control Products
P.O. Box 23 55
90713 Fuerth, Germany

Article No.: DFCP-B10106-00-7600
Dispo 27602 SB 03175.0
Printed in Germany
© 2017 Siemens AG